



H07V2-K



Single-core PVC insulated, non-sheathed power cable with flexible conductor for internal wiring of appliances with a maximum continuous operating temperature of 90 °C.

Rated voltage

U₀/U 450/750 V

Standards

EN 50525-1, EN 50525-2-31, EN IEC 60332-1-2, EN IEC 60228.

European directives

2014/35/UE (LVD) - 2011/65/CE e 2015/863/EU (RoHS).

Conductor

Flexible annealed plain copper class 5 (EN IEC 60228).

Insulation

PVC of type T13. Insulation colour:

blue, dark blue, light blue, black, brown, grey, green/yellow, red, white, turquoise, violet, orange, pink.

Marking

Continuous marking on the insulation: on one side « ICEL H07V2-K IEMMEQU <HAR> ECOGAMMA », on the opposed side « nominal cross section, year of production, MADE IN ITALY ».

Guidance for Use

For fixed and protected installations inside electrical appliances in which the wiring will operate in high temperature areas.

Suitable for fixed protected installation in, or on, lighting or control gear for voltages up to 1000 V a.c. or, up to 750 V d.c. to earth.

If installed in distribution systems the maximum continuous operating temperature shall be limited to 70 °C.

Further instructions and guidance for use are given in the EN 50565 standard.

According to CPR
EN IEC
60332-1-2



Minimum installation and handling temp
+5 °C



Maximum operating temperature on the conductor



Maximum short circuit temperature (max 5 sec)



Minimum usage temperature
-10 °C



Maximum tensile stress
1,5 kg/mm²



Minimum internal bending radii
4 times the overall diameter



Lead Free
Ecogamma



According to
RoHS



H07V2-K



Nominal cross-sectional area of conductor mm ²	Maximum diameter of conductor wires mm	Thickness of insulation specified value mm	Mean overall dimensions		Indicative cable weight g/m	Maximum resistance of conductor at 20 °C ohm/km	Minimum insulation resistance at 90 °C Mohm·km
			MIN mm	MAX mm			
1,5	0,26	0,7	2,8	3,4	22	13,3	0,010
2,5	0,26	0,8	3,4	4,1	33	7,98	0,0095
4	0,31	0,8	3,9	4,8	47	4,95	0,0078
6	0,31	0,8	4,4	5,3	65	3,30	0,0068
10	0,41	1,0	5,7	6,8	110	1,91	0,0065
16	0,41	1,0	6,7	8,1	163	1,21	0,0053
25	0,41	1,2	8,4	10,2	250	0,780	0,0050
35	0,41	1,2	9,7	11,7	339	0,554	0,0043